

## PORTABLE FIRE EXTINGUISHER **ABC DRY POWDER & CO2**

ABC Dry Powder is a multi-purpose, and truly versatile extinguishant suitable for Class A, B, C & Electrical fires.


Available in a wide range of sizes and tested to remarkably high performance fire-ratings in accordance to EN3 standards and Singapore SS 232 Standards, they are suitable for commercial, industrial, and even home usage...etc....

The cylinders are of steel construction, coated with epoxy powder for high corrosion resistance, and fitted with brass valves with pressure gauges.









CO2 Fire Extinguisher is available in Carbon Steel and manufactured in compliance to BS EN3 Standards.



Model	EXT-ABC-2K	EXT-ABC-4K	EXT-ABC-6K	EXT-ABC-9K
Capacity	2 kg	4 kg	6 kg	9 kg
Est. Gross Wt.	3.3 kg	5.9 kg	9.05 kg	10.5 kg
Discharge Time	≥8 sec	≥ 12 sec	≥ 16 sec	≥ 20 sec
Range	≥ 3 m	≥ 3.5 m	≥ 3.5 m	≥ 4 m
Fire Rating	8A / 34B	13A / 70B	21A / 113B	27A / 144B
Dimension	Ø110mm x 295mm (ht)	Ø130mm x 408mm (ht)	Ø168mm x 430mm (ht)	Ø168mm x 542mm (ht)
Working Pressure	12 bar			
Test Pressure	25 bar			
Cyl. Vol.	2.36 litre	4.71 litre	8.47 litre	10.4 litre
Propellant	Dry Nitrogen (N2)			
Finishing	Signal Red – Epoxy Powder Coating			
Standard	Manufactured to EN3 Standards, Singapore Standard SS232 : 1999			

Model	EXT-CO2-2K	EXT-CO2-5k	EXT-CO2-7k	
Capacity	2 Kg	5 Kg	7 Kg	
Est. Gross Wt.	9.5 Kg	18.5 Kg	26 Kg	
Discharge Time	≥ 10 sec	≥ 14 sec	≥ 16 sec	
Range	≥ 3 m			
Fire Rating	21B	34B	55B	
Dimension	Ø114mm x 420mm (ht)	Ø152mm x 570mm (ht)	Ø152mm x 770mm (ht)	
Working Pressure	52 Bar			
Test Pressure	250 Bar			
Cyl. Vol.	3 litre	7.5 litre	10.1 litre	
Propellant	Not Applicable			
Finishing	Signal Red – Epoxy Powder Coating			
Standard	Manufactured to EN3 Standards, Singapore Standard SS232 : 1999			

Due to constant improvement in our products, we reserved the right to modify or withdraw any product or service without prior notice.

Distributed By:-









Version: 08-10-2009